

**ANNEXURE - A (Technical Bid)****PROFORMA TO BE FILLED IN BY THE SUPPLIER / CONTRACTOR**

Date: \_\_\_\_\_

THE PRINCIPAL  
PM SHRI KENDRIYA VIDYALAYA NO. 2  
HINDAN GHAZIABAD UP

Sub: - Checklist for qualification of technical bid and necessary requirement by suppliers/contractors for the year 2024-25.

Sir

With reference to the subject cited above, following is the duly filled checklist along with all self-attested supporting documents towards Technical Bid for **CIVIL (M&R) & BALA RENOVATION WORK** of PM SHRI KENDRIYA VIDYALAYA NO-2, AFS HINDAN GHAZIABAD

S. NO.	APPLICANT/COMPANY DETAILS	
1.	Name of the Firm/Company etc.	
2.	Full Correspondence Address	_____ _____ _____
3.	Name of Owner / Proprietor	
4.	Telephone No. / Mobile No.	
5.	Constitution (Whether Individual / Firm / Company etc.)	
6.	Date of Establishment	
7.	GST No. of Firm	
8.	PAN of Firm	
9.	Bank Details of Firm -	
	Name of Bank	
	Branch Name with Address	
	Account Number	
	IFS Code	
10.	EMD DETAILS as per Tender	
	Name of Bank	
	Demand Draft Number	
	Date of Demand Draft	
	Amount	

11.	<b>Whether enclosed duly signed copy of Tender Notice / Document (Yes / No)</b>	
12.	<b>Experience of working in Kendriya Vidyalayas during the last 5 years for similar works</b>	
i.	<b>2018-19</b>	
ii.	<b>2019-20</b>	
iii.	<b>2020-21</b>	
iv.	<b>2021-22</b>	
v.	<b>2022-23</b>	
13.	<b>Present assignments in hand</b>	
i.		
ii.		
iii.		
iv.		
v.		
14.	<b>Certified copy of Balance Sheet from Chartered Accountant for the last three years</b>	
i.	<b>2020-21</b>	
ii.	<b>2021-22</b>	
iii.	<b>2022-23</b>	

**DECLARATION**

I / We declare that the information furnished above is true to the best of my / our knowledge. I / We undertake to inform PM SHRI KENDRIYA VIDYALAYA NO 2 AFS HINDAN GHAZIABAD, at the earliest about the changes in the details mentioned above. In case of any information / supporting document furnished by me is found to be incorrect / false at any stage of time, the offer of my contract will be cancelled automatically and action may be taken as per KVS Rules. I assure you to provide the best service to the Vidyalaya.

Signature of Supplier / Contractor  
Name: \_\_\_\_\_

Seal

**Annexure – B (Financial Bid)**

**PM SHRI KENDRIYA VIDYALAYA NO. 2 AIR FORCE STATION GHAZIABAD UP - 201004**

**Name of Firm with Address:** \_\_\_\_\_

<b>BUILDING INTERIOR &amp; EXTERIOR PLASTER AND CEMENT MAINTENANCE &amp; REPAIR WORK</b>						
<b>S.NO</b>	<b>DESCRIPTION OF WORK</b>	<b>UNIT</b>	<b>WITHOUT GST RATE</b>	<b>SGST (%)</b>	<b>CGST (%)</b>	<b>TOTAL AMOUNT WITH GST</b>
1.	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete.					
	cement plaster of mix: 1:4 (1 cement: 4 coarse sand)	sqm				
	mm cement plaster of mix: 1:6 (1cement: 6 fine sand)	sqm				
2.	Replacing sandstone slabs in roofing, laid in cement mortar 1:4 (1 cement: 4 coarse sand), including necessary repairs and cement pointing with same mortar complete, including disposal of rubbish to dumping ground, all complete.					
	Red/ white sandstone slabs 30 to 50 mm thick	sqm				
3.	Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40 mm dia M.S tube 1.5 m entre to centre, horizontal & Vertical tubes joining with cup & lock system with M.S tube M.S tube challies M.S clamp and M.S staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it thereafter. The scaffolding system shall be stiffened with bracings runners,	sqm				

	connection with the building etc. wherever required for inspection of work at required locations with essential safety features for the workmen etc. Complete as per directions and approval of Competent Authority. The payment will be made once irrespective of duration of scaffolding. Note: - This item to be used for maintenance work judicially. Necessary dedication for scaffolding in the existing item to be done.					
4.	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50metres lead.					
	for thickness of tiles 10mm to 25mm	sqm				
	for thickness of tiles 25mm to 40mm	sqm				
5.	Providing and laying 60mm thick factory-made cement concrete interlocking paver block of M -30 grade made by block making machine with strong vibratory compaction, of approved size, design & shape, laid in required colour and pattern over and including 50mm thick compacted bed of coarse sand, filling the joints with line sand etc. all complete.	sqm				
6.	Providing and laying factory made chamfered edge Cement Concrete paver blocks in footpath, parks, lawns, drive ways or light traffic parking etc, of required strength, thickness & size/ shape, made by table vibratory method using PU mould, laid in required colour & pattern over 50mm thick compacted bed of sand, compacting and proper embedding/laying of inter locking paver blocks into the sand bedding layer through vibratory compaction by using plate vibrator, filling the joints with sand and cutting of paver blocks as per required size and pattern, finishing and sweeping extra sand all complete.					
	60mm thick cement concrete paver block of M-35 grades with approved colour, design & pattern.	sqm				
	80mm thick C.C. paver block of M-30 grades with approved colour design and pattern.	sqm				

7.	52 mm thick cement concrete flooring with concrete hardener topping, under layer 40 mm thick cement concrete 1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20 mm nominal size) and top layer 12 mm thick cement hardener consisting of mix 1:2 (1 cement hardener mix : 2 graded stone aggregate 6 mm nominal size) by volume, hardening compound mixed @ 2 litre per 50 kg of cement or as per manufacturer's specifications. This includes cost of cement slurry but excluding the cost of nosing of steps etc. complete.	sqm				
8.	Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab, including rubbing and polishing complete with cement mortar 1:4 (1 cement: 4 coarse sand): 25 mm thick.	sqm				
9.	40mm thick rubbed stone flooring over 20mm (average) thick base of cement mortar 1:5 (1cement: 5 coarse sand) including pointing with cement mortar 1:2 (1cement 2 stone dust) admixed with pigment to match the shade of stone and pointing with same	sqm				
10.	Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to IS : 15622, of approved make, in all colours, shades, except White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick Cement Mortar 1:4 (1 Cement : 4 Coarse sand), jointing with grey cement slurry @ 3.3kg/sqm including pointing the joints with white cement and matching pigments etc., complete.	sqm				
11.	Providing and laying Vitrified tiles in different sizes (thickness to be specified by the manufacturer), with water absorption less than 0.08% and conforming to IS: 15622, of approved brand & manufacturer, in all colours					

	and shade, in skirting, riser of steps, laid with cement based high polymer modified quick set tile adhesive (water based) conforming to IS: 15477, in average 6 mm thickness, including grouting of joints (Payment for grouting of joints to be made separately).					
	Size of Tile 600x600 mm	sqm				
	Size of Tile 600x1200 mm	sqm				
12.	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3kg/sqm including grouting the joints with white cement and matching pigments etc., complete.					
	Size of Tile 600x600 mm	sqm				
	Size of Tile 600x1200 mm	sqm				
13.	Grouting the joints of flooring tiles having joints of 3 mm width, using epoxy grout mix of 0.70 kg of organic coated filler of desired shade (0.10 kg of hardener and 0.20 kg of resin per kg), including filling / grouting, and finishing complete					
	Size of Tile 600x600 mm	sqm				
	Size of Tile 600x1200 mm	sqm				
14.	Providing and laying gang saw cut 18 mm thick, mirror polished pre moulded and pre polished machine cut granite stone of required size and shape of approved shade, colour and texture in footpath, flooring cut granite stone of required size and shape of approved shade, colour and texture in footpath, flooring in road side plazas and similar locations, laid over 20mm thick base of cement mortar 1:4 (1cement : 4 coarse sand) including grouting the joints with white cement mixed with matching pigment, epoxy touch ups etc. complete					

	with granite stone of colour black, cherry/ruby red of area less than 0.50 sqm.	sqm				
15.	Marble stone flooring with 18 mm thick marble stone over 20 mm thick cement mortar (1:4) (1cement : 4 coarse sand) including grouting the joints with white cement mixed with matching pigment, epoxy touch ups etc. complete as per direction.	sqm				
16.	Providing and laying gang saw cut 30 mm thick, mirror polished pre moulded and pre polished machine cut granite stone of required size and shape of approved shade, colour and texture in footpath, flooring in road side plazas and similar locations, laid over 20mm thick base of cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement mixed with matching pigment, epoxy touch ups etc. complete.					
	with granite stone of colour black, cherry/ruby red of area less than 0.50 sqm.	sqm				
17.	Providing and laying matt finished vitrified tile of size 300x300x9.8mm having with water absorption less than 0.5% and conforming to IS: 15622 of approved make in all colours and shades in for outdoor floors such as footpath, court yard, multi modals location etc., laid on 20mm thick base of cement mortar 1:4 (1 cement : 4 coarse sand) in all shapes & patterns including grouting the joints with white cement mixed with matching pigments etc. complete.	sqm				

We agree to supply the above goods in accordance with the specification for the above mention unit price shown against the items for which quotations have been submitted within the period specified in the invitation for quotations.

(BIDDER)

SEAL OF FIRM'S

DATE: .....

SIGNATURE

NAME: .....

**Annexure – B (Financial Bid)**

**PM SHRI KENDRIYA VIDYALAYA NO. 2 AIR FORCE STATION GHAZIABAD UP - 201004**

**Name of Firm with Address:** \_\_\_\_\_  
\_\_\_\_\_

<b>INTERIOR &amp; EXTERIOR WHITEWASH PAINTING ITEMS AND MAINTENANCE &amp; REPAIR WORK</b>						
<b>S.NO</b>	<b>DESCRIPTION OF WORK</b>	<b>UNIT</b>	<b>WITHOUT GST RATE</b>	<b>SGST (%)</b>	<b>CGST (%)</b>	<b>TOTAL AMOUNT WITH GST</b>
1.	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	sqm				
2.	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	sqm				
3.	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	sqm				
4.	With ready mixed pink or grey primer on wood work (hard and soft wood) having VOC content less than 50 grams/ litre	sqm				
5.	With water thinnable cement primer on wall surface having VOC content less than 50 grams/litre	sqm				
6.	Distemping with dry distemper of approved brand and manufacture (one or more coats) and of required shade on old work to give an even	sqm				



	shade.					
7.	Distempering with 1st quality acrylic distemper (Ready mix) having VOC content less than 50 grams/ litre of approved brand and manufacture to give an even shade :					
	old work (one or more coats)	sqm				
8.	Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour.					
	one coat	sqm				
	two coats	sqm				
9.	Wall painting with premium acrylic emulsion paint of interior grade, having VOC (Volatile Organic Compound) content less than 50 grams/ litre of approved brand and manufacture, including applying additional coats wherever required to achieve even shade					
	one coat	sqm				
	two coat	sqm				
10.	Distempering with 1st quality acrylic distemper, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour.					
	one coat	sqm				
	two coats	sqm				
11.	Painting (two or more coats) on rainwater, soil waste and vent pipes and fittings with black anticorrosive bitumastic paint of approved					

	brand and manufacture, over and including a priming of ready mixed zinc chromate yellow primer on new work:					
	100 mm diameter pipes	metre				
	150 mm diameter pipes	metre				
12.	Painting (two or more coats) on rain water, soil waste and vent pipes and fittings with synthetic enamel paint of approved brand and manufacture and required colour over a priming coat of approved steel primer.					
	100 mm diameter pipes	metre				
	150 mm diameter pipes	metre				
13.	Painting on G.S. sheet with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade	sqm				
	New work (two or more coats) including a coat of approved steel primer but excluding a coat of mordant solution	sqm				
	Applying a coat of mordant solution on G.S. sheet	sqm				
14.	White wash with lime to give an even shade:					
	old work (two or more coats)	sqm				
	old work (one or more coats)	sqm				
15.	Painting with oil type wood preservative of approved brand and manufacture: Old work (one or more coats)	sqm				
16.	Wall painting with plastic Emulsion paint of approved brand and manufacture to give an even shade: One or more coats on old work	sqm				
17.	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade : one or more	sqm				

	coatson old work					
18.	Painting with aluminium paint of approved brand and manufacture to give an even shade: one or more coats on old work	sqm				
19.	Painting with black anti-corrosive bitumastic paint of approved brand and manufacture to give an even shade : 13ne or more coats on old work	sqm				
20.	Polishing on wood work with readymade wax polish of approved brand and manufacture old work	sqm				
21.	Painting (one or more coats) with black Japan paint of approved brand and manufacture to give an even shade.	sqm				
22.	Finishing walls with water proofing cement paint of required shade :					
	old work (one or more coats applied @ 2.20 kg/10 sqm) over priming coat of primer applied @ 0.80 litres/10 sqm complete including cost of Priming coat.	sqm				
	old work (one or more coats @ 2.20 kg/10 sqm) complete.	sqm				
23.	Finishing walls with textured exterior paint of required shade :					
	old work (Two or more coats on existing cement paint surface applied @ 3.28 ltr/10 sqm	sqm				
	old work (One or more coats) applied @ 1.82 ltr/10 sqm.	sqm				
24.	Finishing walls with Acrylic Smooth exterior paint of required shade:					
	old work (Two or more coat applied @ 1.67 ltr/ 10 sqm) on existing cement paint surface	sqm				
	old work (One or more coat applied @ 0.90 ltr/10 sqm).	sqm				
25.	Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade					

	old work (Two or more coats applied @ 1.43 ltr/ 10 sqm) over existing cement paint surface	sqm				
	old work (one or more coats applied @ 0.83 ltr/10 sqm)	sqm				
26.	Varnishing with varnish of approved brand and manufacture					
	one or more coats with copal varnish	sqm				
	one or more coats with spar varnish	sqm				
27.	Bala Renovation work for wall, door, art painting work	sqft				
28.	Melamine polishing on woodwork (one or more coat).	sqm				
29.	Varnishing with flatting varnish of approved brand and manufacture one or more coats on old work.	sqm				
30.	Providing Samocem on exterior walls of the building	P. Ltr.				
31.	Providing Oil Bond Distemper	P. Ltr.				
32.	Providing exterior paint (Apex Paint)	P. Ltr.				
33.	Providing White color wash lime powder	P. Ltr.				
34.	Providing Cement Primer	P. Ltr.				
35.	Providing MS Steel (oxide) primer	P. Ltr.				
36.	Providing Plastic Paint	P. Ltr.				
37.	Providing Sealer for polishing wooden surface	P. Ltr.				
38.	Providing Tarpin Oil	P. Ltr.				
39.	Providing Enamel Paint	P. Ltr.				
40.	Providing Thinner	P. Ltr.				

41.	Providing Brush 5"	Each				
42.	Providing Old Dhoti	Each				
43.	Providing Send Paper	Each				
44.	Providing Painting Skilled Labour (Per Person)	P. Day				
45.	Providing Painting Unskilled Labour (Per Person)	P. Day				
46.	Providing Plaster of Paris	per kg				
47.	Providing Chalk Mitti	per kg				
48.	Providing Fevicol DDL	per kg				

We agree to supply the above goods in accordance with the specification for the above mention unit price shown against the items for which Quotations have been submitted within the period specified in the invitation for quotations.

(BIDDER)

SEAL OF FIRM'S

DATE: .....

SIGNATURE

NAME: .....

**Annexure – B (Financial Bid)**

**PM SHRI KENDRIYA VIDYALAYA NO. 2 AIR FORCE STATION GHAZIABAD UP - 201004**

**Name of Firm with Address:** \_\_\_\_\_  
\_\_\_\_\_

<b>IRONANDALUMINIUM FABRICATION MAINTENANCE &amp; REPAIR WORK</b>						
<b>S.NO</b>	<b>DESCRIPTION OF WORK</b>	<b>UNIT</b>	<b>WITHOUT GST RATE</b>	<b>SGST (%)</b>	<b>CGST (%)</b>	<b>TOTAL AMOUNT WITH GST</b>
1.	Providing and laying in position specified grade of Aluminium Bombay sliding Section window work Double door window fixing window including cost of finishing specifications: - Bombay slides Aluminium section 16swg2½ X 1½ Section window frame Clear glass 5mm Aluminium weeding Heavy/ EPDM rubber/Neoprene gasket/ handle/ tower bolt / etc	sq.ft				
2.	Providing and laying in position specified grade of Aluminium Partition work including cost of finishing specifications: -Aluminium section 16swg 2½ X 1½ Section Partition frame Aluminium weeding Heavy / Clear glass 5mm/ both side Laminate board 12mm/ EPDM rubber/Neoprene gasket	sq.ft				
3.	Providing and laying in position specified grade of Aluminium Door with frame work including cost of finishing specifications: - Aluminium section 16swg 2½ X 1½ Section Door frame Clear glass	sq.ft				

	5mm/ both side Laminate board 12mm/ EPDM rubber/Neoprene gasket / tower bolt door closer/ Handle/ Lock/ etc					
4.	Providing and fixing of Steel 10x14 dustbin with carom finish perforated round rubber bass heavy gage dustproof	Each				
5.	Providing and fixing of Steel 14x28 dustbin with carom finish perforated round rubber bass heavy gage dustproof	Each				
6.	Providing and fixing of mirror glass 5mm with wooden frame back ply with paint	sq.ft				
7.	Supplying / fixing of table top Clear glass 8mm	sq.ft				
8.	Providing and fixing E-Class Room Projector safety Security Cover Steel work in built up tubular trusses including cutting/ hosting fixing with fastners etc in position and applying a painting and priming coat of approved steel primer welded and bolted including special shaped washers specifications: 1"x1" jalli 3/4" Angle 3/4" Tee Size 18"x16"x16"	Each				
9.	Providing and fixing of Honours Board/School Name Board Including cost of finishing made of 9mm thick Ply 3mm Colour ACPSheet frame Computerise golden writing with School Logo 4 hooks for hanging	sq.ft				
10.	Providing and fixing Student safety Security Steel work in built up tubular trusses including cutting/ hosting fixing with fastners etc in position and applying a painting and priming coat of approved steel primer welded and bolted including special shaped washers etc as per the following specifications:- Water cooler cover Angle Door frame 35mmX35mmX5mm /Mash 25mm X 25mm Iron patti	sq.ft				
11.	Providing and fixing Student safety Security Steel work in built up tubular trusses including cutting/ hosting fixing with fastners etc in position and applying a painting and priming coat of approved steel	sq.ft				

	primer welded and bolted including special shaped washers etc as per the following specifications: - iron Door angel 35X35X5 Door frame CRC sheet 16swg/ Iron Patti 25mmX3mm/ Hinges/ Tuber Bolt 09inch Attach drawing					
12.	Providing and fixing Student safety Security Steel work in built up tubular trusses including cutting, hosting fixing with fastners etc. in position and applying a painting and priming coat of approved steel primer welded and bolted including special shaped washers etc. as per the following specifications: - iron Door 2”X1” tube CRC sheet 16swg, Iron 1”, 1/2” Patti, 6mm sariya, Hinges, Tuber Bolt 09inch	sq.ft				
13.	Temporary Iron shed work in built up tubular trusses including cutting/ hosting fixing with fastners etc in position and applying a painting and priming coat of approved steel primer welded and bolted including special shaped washers etc as per the following specifications: - Base pipe 4” Round 16swg Base plate 8mm 2”round Pipe 16swg, 1½ ” Round pipe 16swg, 2” Square pipe 16swg, J hooks, Self-Drilling screws G.I metro sheet Attach Drawing	sq.ft				
14.	Temporary Iron shed Repair work in built up tubular trusses including cutting/ hosting fixing with fastners etc in position and applying a painting and priming coat of approved steel primer welded and bolted including special shaped washers etc as per the following specifications: New G.I metro sheet J hooks welding	sq.ft				
15.	Providing and fixing Student safety Security Steel work in built up tubular trusses including cutting/ hosting fixing with fastners etc in position and applying a painting and priming coat of approved steel primer welded and bolted including special shaped washers etc as per the following specifications: -Iron angle frame 25X25X3 square sariya 6mm school corridors covered of open areas	sq.ft				



16.	Providing and fixing Student safety Security Steel work in built up tubular trusses including cutting/ hosting fixing with fastners etc in position and applying a painting and priming coat of approved steel primer welded and bolted including special shaped washers etc as per the following specifications: -Iron angle frame 25X25X3 Iron Jali 25mmx25mm Iron patti 19mmx3mm school corridors covered of open areas	sq.ft				
17.	Providing and fixing of Steel frame School Name Board Including cost of finishing made of 1¼ inch round Steel Pipe & ½ inch round steel pipe / frame pipe 1inch X 1inch square pipe thick 16swg steel base plate 4mm and 3mm Colour AB Sheet Computerise writing with School Logo	sq.ft				
18.	Providing and fixing Student safety Security Steel Pipe Handrail Options for staircases work in built up tubular trusses including cutting, hosting fixing with fastners etc. welded and bolted including special shaped washers etc. as per the following specifications: - Steel Round Pipe a Handrail Options for staircases work school stair Steel Round Pipe 1¼” 16swg and side breaket	R.mtr				
19.	Providing / Laying / fixing in position specified grade of House Block Name board with 1¼ inch round pipe base plate Retro Reflective sign board ACP sheet complete board size 2ftX1½ftX5ft	Each				
20.	Providing and fixing flower pot step by step Iron stand specifications:- 1”X1” Iron Square Pipe 1” iron patti 12” step with paint size Length 4ft two step stand	Each				
21.	Providing and fixing School Boundary wall Fencing work (Barbed wire punched tape concertina coils 24inch G.I wires 35×35×5 24inch Iron Angle hits Y shape Angle work in built up tubular trusses	R.mtr				

	including cutting, hosting fixing etc. in position and applying a painting and priming coat of approved steel primer etc.					
23.	Student safety Security Steel work in built up tubular trusses including cutting/ hosting fixing with fastners etc in position and applying a painting and priming coat of approved steel primer welded and bolted including special shaped washers etc as per the following specifications: - Play Ground open area cover work iron Angle Frame 35mmX35mmX5mm, Mash 25mmX25mm Iron Patti	sq.ft				
24.	Student safety Security Providing and fixing Iron work in built up tubular trusses including cutting/ hosting fixing with fastners etc in position and applying a painting and priming coat of approved steel primer welded and bolted including special shaped washers etc as per the following specifications: - Garden Area Iron Grill work Angle Frame 35mmX35mmX5mm, 8mm Square sariya Iron Patti	sq.ft				
25.	Student safety Security Providing and fixing Iron work in built up tubular trusses including cutting/ hosting fixing with fastners etc in position and applying a painting and priming coat of approved steel primer welded and bolted including special shaped washers etc as per the following specifications:- open drainage cover work Iron Angle 35X35X5 outer frame 1¼” X 1¼” Iron Patti	9”X60”	Each			
		12”X60”	Each			
		18”X60”	Each			

We agree to supply the above goods in accordance with the specification for the above mention unit price shown against the items for which quotations have been submitted within the period specified in the invitation for quotations.

(BIDDER)

SEAL OF FIRM’S

DATE: .....

SIGNATURE

NAME: .....